



MATERIAL SAFETY DATA SHEET

Components: TIN / LEAD / ANTIMONY / ACID ROSIN
MSDS Number: MSDS-09
Preparation date: July, 2015
Revision date: January, 2021
Revision Level: 03

NA = Not Applicable

NE = Not Established

NAV = Not Available

Section 1.- Product and company identification

Trade Name:

Omega® Tin-Lead-Antimony solder with Acid Rosin wire of different diameters, it applies to all part numbers with this alloy and resin type.

Product Name:

As indicated on the label.

Manufacturer:

Omega Aleaciones, S.A. de C.V.

Eje 132 No. 120 Zona Industrial
San Luis Potosí, S.L.P. C.P. Zip code 78395
México

E-mail: calidad@omegaaleaciones.com

Phone Number: +52 (444) 824 00 03

Fax: +52 (444) 824 11 73

Main purpose:

As solder in the metalworking and electronics industries.

Section 2.- Hazard identification

2.1 Classification of the substance or mixture

Health hazard



GHS07
GHS07



GHS08



Omega® Tin-Lead-Antimony Solder with Acid Rosin

H302: Harmful if swallowed. Acute Tox. 4.
H332: Harmful if inhaled. Acute Tox.4.
H317: May cause an allergic skin reaction. Skin Sens. 1.

GHS08

H351: Suspected of causing cancer. Carc. 2.
H360: May damage fertility or the unborn child. Repr. 1.
H373: May cause damage to organs through prolonged or repeated exposure. STOT RE 2.

STOT RE: Specific target organ toxicity- repeat exposure

2.2 Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS07



GHS08

Signal word: **Danger**

Hazard statements

H317: May cause an allergic skin reaction.
H351: Suspected of causing cancer.
H360: May damage fertility or the unborn child.
H373: May cause damage to organs through prolonged or repeated exposure.
H302+H332: Harmful if swallowed or if inhaled.

Precautionary statements

P260: Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264: Wash thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.
P302 + P352: IF ON SKIN: Wash with plenty of water.
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301 + P312: IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313: IF exposed or concerned: Get medical advice/ attention.
P333 + P313: IF skin irritation or rash occurs: Get medical advice/ attention.
P405: Store locked up.
P501: Dispose of contents/ container in accordance with local/ regional/ national/ international regulations.

OSHA/HCS status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Emergency Overview	WARNING!



Omega® Tin-Lead-Antimony Solder with Acid Rosin

	<p>CAUSE EYE IRRITATION, SKIN AND RESPIRATORY TRACT. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER. It irritates the eyes, skin and respiratory tract. Avoid contact with eyes, skin and clothing. Do not breathe the dust. Use only with adequate ventilation. Keep the container tightly closed and sealed until the time of its use. Wash thoroughly after handling. Avoid exposure during pregnancy. Avoid contact of the spilled material with ground and surface waters.</p>
Routes of entry	Inhalation and Ingestion.

Potential acute health effects	
Eyes	Irritating to eyes.
Skin	Irritates the skin.
Inhalation	Inhalation of this or other welding products can cause headache, nausea, and muscle pain.
Ingestion	Ingestion of this or other welding products can cause headache, nausea, and muscle pain.
Medical conditions aggravated by overexposure	Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by overexposure to this product. Prolonged or repeated exposure due to the ingestion may cause anemia, insomnia, weakness, constipation and abdominal pain (California Health & Safety Code 25249.5 et seq).
Chronic	<p>TIN: It has been shown to increase the incidence of sarcoma in animal tests.</p> <p>LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic with lead poisoning. The symptoms of lead poisoning include headache, nausea, abdominal pain, muscular and articular pain and damage to the nervous system, circulatory system and the kidneys. Lead can be harmful to the fetus.</p> <p>ANTIMONY: abdominal cramps and pain, metal fume fever, cough, chills, tremors, muscle weakness. Prolonged or repeated contact may cause dermatitis. Chronic effects are dizziness or can cause dizziness, drowsiness or fatigue and anorexia. May cause adverse reproductive effects in women.</p>

Section 3.- Composition and information on components

COMPONENT	C. A. S. NUMBER	WEIGHT %	OSHA PEL	ACGIH TLV
Tin	7440-31-5	1.0 - 99.0	2.0 mg/m ³	2.0 mg/m ³
Lead	7439-92-1	1.0 - 99.0	0.05 mg/m ³	0.05 mg/m ³
Antimony	7440-36-0	0.3 - 5.0	0.5 mg/m ³	0.5 mg/m ³
Acid Rosin or Zinc Chloride	7646-85-7	0.5 - 3.3	1 mg/m ³	1 mg/m ³

Section 4.- First aid measures

Skin:
MOLTEN PRODUCT: In case of contact, immediately place bags of cold water for at least 15 minutes. Do not put ice directly on the skin. Do not attempt to remove the solidified product of the skin, this could cause damage. Get medical attention immediately.



Omega® Tin-Lead-Antimony Solder with Acid Rosin

SOLID PRODUCT: In case of contact, immediately wash skin with soap and plenty of water while removing contaminated clothing and shoes. Wash the clothing before wearing again. Clean the shoes completely before returning it to use. Use lotion to prevent dryness. Get medical attention if irritation persists.

Eyes:

MOLTEN PRODUCTS: Wash the burns with plenty of water at low pressure. Get immediate medical attention.

SOLID PRODUCT: Check if the victim takes contact lenses and in this case, withdraw them from it. Wash thoroughly with water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention if irritation develops.

Inhalation:

Move to the affected person in the open air. If you are experiencing the symptoms of overexposure, evacuate to the fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen everything that might be tight, as the collar of a shirt, tie or belt. Get medical attention immediately.

Ingestion:

Wash out mouth with water. If the person is conscious, immediately give 2 glasses of water. Do not induce vomiting unless directed to do so by medical personnel. Do not give anything by mouth to an unconscious person. Get medical attention immediately.

Protection of first-aiders:

Do not take any action that involves some personal risk or that does not provide for adequate training. If it is suspected that the vapors are still present, the person in charge of the rescue you must use an appropriate mask or a self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Notes to physician:

Not available.

Section 5.- Fire fighting measures

Flammability of the product	May be combustible at high temperatures.
Hazardous thermal decomposition products	Decomposition products may include the following materials: May free zinc chloride and chlorine. Carbon dioxide. Carbon monoxide. Metal oxide/oxides.
Extinguishing media Suitable	Use an extinguishing agent suitable for the surrounding fire. Alcohol foam, carbon dioxide or dry chemical.
Not suitable	None known.
Special exposure hazards	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. No specific fire or explosion. Closed containers may explode when exposed to fire.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus with a full face-piece operated in positive pressure mode.

Section 6.- Accidental release measures



Omega® Tin-Lead-Antimony Solder with Acid Rosin

If the material is in its solid state, pick up and reuse. When molten, allow to solidify, and reuse if it is not contaminated. If contaminated, refer to section 13 for disposal information.

Personal precautions:

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up:

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7.- Handling and storage

Handling:

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Avoid contact with eyes, skin and clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container.

Containers:

Empty containers retain product residue and can be hazardous (solids or vapors). Note the precautions in the boxes. Do not expose the containers to heat or flames. Use appropriate containment to avoid environmental contamination.

Storage:

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep the container away from sources of ignition. Do not store in unlabeled containers.

Other storage conditions:

The lifetime of tin base (non-ferrous) solders in solid form (bars and wires) is very long; as long as it is kept in its original packaging and under controlled storage conditions, mainly avoiding moisture and dust.

Applying direct heat is the only thing that can modify its shape and physical properties.

After 5-10 years it can only lose its shine, but not its functionality.

It is recommended that the relative humidity of the storage area for welding consumables does not exceed 60%, if the ambient temperature falls below 15 ° C. The storage temperature should be kept about 2 degrees above room temperature. The reason for this recommendation is to avoid moisture condensation on the consumables. It is important that the storage area is dry.

Recommended storage temperature: 10 ° C to 40 ° C.

Hygiene practices in the workplace:



Omega® Tin-Lead-Antimony Solder with Acid Rosin

Wash hands thoroughly after handling welding, before eating or smoking.

Section 8.- Exposure controls and personal protection

Engineering measures

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protection

Eyes:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Respiratory:

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a NIOSH approved respirator when necessary.

Hands:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Skin:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Ventilation:

Have adequate ventilation to keep exposure below the limits of allowable concentration in the air.

Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Product name	Exposure limits
Tin	<p>ACGIH TLV (United States, 1/2005). TWA: 2 mg/m³ 8 hour(s). State: All forms.</p> <p>NIOSH REL (United States, 12/2001), Notes: The REL and PEL also apply to other inorganic tin compounds (as Sn) except tin oxides. TWA: 2 mg/m³ 10 hour(s). State: All forms.</p> <p>OSHA (United States, 0/1997). Notes: Respirable. TWA: 2 mg/m³</p> <p>NIOSH (United States, 0/1994). Notes: Respirable. TWA: 2 mg/m³ STEL: 4 mg/m³</p>
Lead	<p>NIOSH (REL): 0.050 mg/m³ (TWA), 100 mg/m³ (IDLH).</p> <p>ACGIH (TLV): 0.05 mg/m³ (TWA).</p> <p>OSHA (PEL): 50 µg/m³ (TWA).</p>



Omega® Tin-Lead-Antimony Solder with Acid Rosin

	30 µg/m ³ (Action Level, See 29 CFR 1910.1025)
Antimony	<p>ACGIH TLV (United States, 3/2012). Notes: As Sb. TWA: 0.5 mg / m³ (as Sb) 8 hour (s).</p> <p>OSHA PEL (United States, 6/2010). Notes: As Sb. TWA: 0.5 mg / m³ (as Sb) 8 hour (s).</p> <p>OSHA PEL 1989 (United States, 3/1989). Notes: As Sb. TWA: 0.5 mg / m³ (as Sb) 8 hour (s).</p> <p>NIOSH REL (United States, 6/2009). Notes: The REL and PEL also applies to other compounds of antimony (Sb). TWA: 0.5 mg / m³ (as Sb) 10 hours (s).</p>

Components	Nº CAS - Nº EINECS	PEL mg/m ³	TLV-TWA mg/m ³	TLV-STEL mg/m ³
TIN	7440-31-5/231-141-8			
	(USA)	2	2	-
	(EU)	-	2	4
	(Canada)	-	2	4
LEAD	(Singapore)	2	-	-
	7439-92-1/231-100-4			
	(USA)	0.05	0.05	-
	(EU)	-	0.15	-
	(Canada)	-	0.05	-
	(Singapore)	0.15	-	-
ANTIMONY	(Mexico)	-	0.15	-
	(China)	-	0.05 (dust)	-
			0.03 (steam)	
	7440-36-0/231-146-5			
	(USA)	0.5	0.5	-
	(EU)	0.5	-	-
	(Canada)	-	0.5	1.5
	(Mexico)	-	5	-
(Singapore)	0.5	-	-	
(China)	-	0.5	-	

EU = Occupational Exposure Limits of the European Union.

Section 9.- Physical and chemical properties

General data	
Physical state:	Solid
Shape:	Wire
Color:	Silver Grey
Odor:	Odorless
Valor pH:	NAV
Melting point:	361 °F or 183 °C
Boiling point:	3164 °F or 1740 °C
Flash point and method:	NAV
Flammability (solid, gas):	NAV
Flammable limits:	NAV
Vapor pressure:	NAV
Vapor density:	NAV



Omega® Tin-Lead-Antimony Solder with Acid Rosin

Specific gravity:	7.8
Density:	NAV
Autoignition temperature:	NAV
% Volatile:	NAV
Evaporation rate:	< 1
Dispersibility properties:	NAV
Solubility:	Partially soluble in the following materials: NAV Slightly soluble in the following materials: water. Insoluble in the following materials: NAV

Section 10.- Stability and reactivity

Stability and reactivity	The product is stable.
Incompatibility with various substances	Reactive or incompatible with the following materials: bases and strong acids, oxidants, sulfur and halogens.
Hazardous decomposition products	May free zinc chloride, chlorine, smoke and toxic metal oxides.
Hazardous polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions of reactivity	NAV

Section 11.- Toxicological information

Toxicity data				
Product name or Ingredient	Test	Result	Route	Species
Tin	LD50	2000 mg/kg	oral	rat
	LD50	2000 mg/kg	dermal	rabbit
	LDLO	388 mg/kg	oral	duck
Lead	LDLO	160 mg/kg	oral	pigeon
Antimony	LD50	7000 mg/kg	oral	rat
Zinc Chloride	LD50	1100 mg/kg	oral	rat

Chronic effects on humans	Classified None. By NIOSH [Tin]. Classified A3 (Proven for animals.) By ACGIH, 2B (Possible for humans.) By IARC [Lead]. Classified 2 (Reasonably anticipated to be human carcinogens.) By NTP [Lead]. Classified None. By NIOSH [Lead]. Classified 4 (Probably not for humans.) By IARC, None. Classified None. By NIOSH [Antimony]. Contains damage to the following organs: blood, kidneys, lungs, spleen, brain, digestive system, gastrointestinal tract, upper respiratory tract, skin and eyes. It is harmful to the central nervous system (CNS) and the reproductive system.
Other toxic effects on humans	Slightly hazardous by the following route of exposure: (irritant, sensitizer) skin contact, eye contact (irritant), of ingestion, of inhalation. Not corrosive to skin. Not absorbed through the skin.

Specific effects	
Carcinogenic effects	Contains material which may cause cancer. The risk of cancer depends on duration and level of exposure.
Mutagenic effects	This product, when used for soldering and similar applications, produces chemicals that cause birth defects.
Teratogenicity / Reproductive toxicity	This product, when used for soldering and similar applications, produces chemicals that cause reproductive harm.



Section 12.- Ecological information

Environmental precautions	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Products of degradation	Products of degradation: carbon oxides (CO, CO ₂) and water. Metal oxides.
Toxicity of the products of biodegradation	The products of degradation are more toxic than the product itself.

Ecotoxicity data			
Product name or ingredient	Species	Period	Result
Lead	Daphnia magna (EC50)	48 hours	600 µg/L
	Daphnia magna, Ceriodaphnia dubia (LC50)	48 hours	0.074-0.656 mg/L
	Daphnia magna, Ceriodaphnia dubia (LC50)	48 hours	0.029-1.18 mg/L
	Daphnia magna, Ceriodaphnia dubia (LC50)	48 hours	0.026-3.12 mg/L
	Pseudokirchneriella subcapitata, Chlorella kessierii (EC50)	72 hours	0.072-0.388 mg/L
	Pseudokirchneriella subcapitata, Chlorella kessierii (EC50)	72 hours	0.026-0.080 mg/L
	Pseudokirchneriella subcapitata, Chlorella kessierii (EC50)	72 hours	0.021-0.050 mg/L
	Pimephales promelas (LC50)	96 hours	0.298 mg/L
	Cyprinus carpio (LC50)	96 hours	0.44 mg/L
	Oncorhynchus mykiss (LC50)	96 hours	471 mg/L
	Oncorhynchus mykiss (LC50)	96 hours	542 mg/L
	Oncorhynchus mykiss (LC50)	96 hours	1.17 mg/L
	Oncorhynchus mykiss (LC50)	96 hours	1.32 mg/L
	Pimephales promelas, Oncorhynchus mykiss (LC50)	96 hours	0.041 - 1.810 mg/L
	Pimephales promelas, Oncorhynchus mykiss (LC50)	96 hours	0.052 - 3.60 mg/L
	Pimephales promelas, Oncorhynchus mykiss (LC50)	96 hours	0.114-3.25 mg/L
	Gambusia affinis (LC50)	96 hours	56000 mg/L
	Antimony	Cyprinodont variegates (LC50)	96 hours

Environmental Impact Data: (percentage by weight)					
CFC:	HFC:	Cl. Solv:	VOC:	HCFC	ODP
0	0	0	0	0	0

Section 13.- Disposal considerations

Waste disposal

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Omega® Tin-Lead-Antimony Solder with Acid Rosin

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations (refer to section 7 and Section 8).

If hazardous under 40 CFR 261, subparts b and c, material must be treated or disposed in a facility meeting the requirements of 40 CFR 254 or 265. If non-hazardous, material should be disposed in a facility meeting the requirements of 40 CFR 257. These criteria apply E.U.A. To classify the type of material in Mexico should refer to the Official Mexican Standard NOM-052-SEMARNAT-2005.

Resource Conservation and Recovery Act (RCRA), Status of Unused Material: If discharged in unaltered form, material should be tested to determine if it must be classified as a hazardous waste for disposal purposes. Under specific circumstances, application can be made to the EPA administrator to have a particular waste designated non-hazardous.

Section 14.- Transport information

Regulatory information	ONU number	Proper shipping name	Class	PG*	Label	Additional information
DOT Classification	Not regulated	-	-		-	-
TDG Classification	Not regulated	-	-		-	-
ADR/RID Class	Not available	-	-		-	-
IMDG Class	Not regulated	-	-		-	-
IATA-DGR Class	Not regulated	-	-		-	-

PG*: Packing group.

Ground	Not regulated
Air	Shipper must be trained and certified. Refer to IATA Dangerous Goods Regulations. UN Number: None. UN Pack Group: NA. UN Class: Non Hazardous. ICAO/IATA: Non Hazardous. Shipping Name: Non Hazardous.
Sea	Not regulated

DOT (Department of Transportation).

Proper Shipping Name: Not regulated by DOT.

Section 15.- Regulatory information

United States	
HCS Classification	Toxic material. Carcinogen. Target organ effects.
USA Federal regulations	TSCA 6 proposed risk management: Lead. TSCA 8(a) PAIR: Antimony. TSCA 8(a) IUR: Partial exemption. TSCA 8(b) Inventory: Tin; Lead. TSCA 8(d) H and S data reporting: Antimony, October 4, 1992. TSCA 12 (b) annual export notification: Lead. United States inventory (TSCA 8b): Not determined.



Omega® Tin-Lead-Antimony Solder with Acid Rosin

	<p>SARA 302/304/311/312 extremely hazardous substances: No products were found.</p> <p>SARA 302/304 emergency planning and notification: No products were found.</p> <p>SARA 302/304/311/312 hazardous chemicals: Tin; Lead; Antimony.</p> <p>SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Tin: Immediate (acute) health hazard; Lead: Delayed (chronic) health; Antimony: Immediate (acute) health hazard, Delayed (chronic) health hazard.</p> <p>Clean Water Act (CWA) 307: Antimony.</p> <p>Clean Water Act (CWA) 311: No products were found.</p> <p>Clean Air Act (CAA) 112 accidental release prevention: No products were found.</p> <p>Clean Air Act (CAA) 112 regulated flammable substances: No products were found.</p> <p>Clean Air Act (CAA) 112 regulated toxic substances: No products were found.</p> <p>SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4): Reportable ingredients: Lead CAS# 7439-92-1.</p> <p>TSCA (Toxic Substances Control Act of 1976, USA): All substances are TSCA listed or exempt from listing.</p> <p>CAA (Clean Air Act, USA): This product does not contain any class 1-ozone depletors. This product does not contain any class 2-ozone depletors. This product does not contain any chemicals listed as hazardous air pollutants.</p> <p>California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, May 1, 1997 revision, USA): This product contains Lead a chemical known to the state to cause reproductive toxicity and cancer.</p> <p>EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45): This product contains the following chemicals subject to the reporting requirements of Section 313 of Title III of the SARA of 1986 and 40 CFR part 372: Lead CAS # 7439-92-1.</p>
--	---

SARA 313			
	Product name	CAS number	Concentration
Form R - Reporting requirements	Lead	7439-92-1	80 - 100
	Antimony	7440-36-0	1 - 5
Supplier notification	Lead	7439-92-1	80 - 100
	Antimony	7440-36-0	1 - 5

SARA 313 notifications must not be detached from the Material Safety Data Sheets (MSDS) and any copying and distribution shall include copying and distribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations of the USA	<p>Connecticut Carcinogen Reporting: None of the components are listed.</p> <p>Connecticut Hazardous Material Survey: None of the components are listed.</p> <p>Florida Substances: Tin, Antimony, Lead.</p> <p>Illinois Chemical Safety Act: None of the components are listed.</p> <p>Illinois Toxic Substances Disclosure to Employee Act: None of the components are listed.</p> <p>Louisiana Reporting: None of the components are listed.</p> <p>Louisiana Spill: None of the components are listed.</p> <p>Massachusetts Spill: None of the components are listed.</p> <p>Massachusetts RTK Hazardous Substances: Tin, Antimony, Lead.</p> <p>Michigan Critical Material: Antimony, Lead.</p> <p>Minnesota Hazardous Substances: Tin, Antimony, Lead.</p> <p>New Jersey Hazardous Substances: Antimony, Lead.</p>
-------------------------------------	--



Omega® Tin-Lead-Antimony Solder with Acid Rosin

	<p>New Jersey Spill: Tin.</p> <p>New Jersey Toxic Catastrophe Prevention Act: None of the components are listed.</p> <p>New Jersey RTK Hazardous Substances: Tin, Antimony, Lead.</p> <p>New York Acutely Hazardous Substances: Lead, Antimony.</p> <p>New York Toxic Chemical Release Reporting: None of the components are listed.</p> <p>Pennsylvania RTK Hazardous Substances: Tin, Antimony, Lead.</p> <p>Rhode Island Hazardous Substances: Tin, Antimony, Lead.</p>
--	---

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Lead	Yes	Yes	15 µg/day (ingestion) 0.0005 µg/day (inhalation)	Yes

Section 16.- Other information

References:

- ACGIH, Threshold Limit Values, 1994-1995.
- IATA, Dangerous Goods Regulations, 37th edition (January 1, 1996).
- NFPA, Fire Protection Guide to Chemical Hazards, 11th edition.
- NIOSH, Pocket Guide to Chemical Hazards, revision June 1994.
- TSCA (Toxic Substance Control Act), Chemical Substance Inventory List, 1985.
- CFR29, OSHA's Permissible Exposure Limits, revision July, 1993.
- CFR29, part 1910.1200, Hazard Communication.
- CHEMTOX database.
- Canada Gazette Part II, Vol. 122, No. 2 Registration SOR/88-64 31 December, 1987 Hazardous Products Act "Ingredient Disclosure List".
- CSST (Commission de Santé et Sécurité au Travail), document #RT-12: Classification of Certain Chemical Substances.
- CRC Handbook of chemistry and physics, 67th edition, CRC Press Inc., Boca Raton, Florida.
- Sigma-Aldrich handbook of fine chemicals, 1998.
- The United Nations Economic Commission for Europe. Globally Harmonized System of Classification and Labelling of Chemicals (GHS), Rev 5, 2013.
- Mexican Official Standards
 - NOM-004-SCT2-2008, Sistema de identificación de unidades destinadas al transporte terrestre de materiales y residuos peligrosos.
 - NOM-005-STPS-1998, Relativa a las condiciones de seguridad en los centros de trabajo para el manejo, transporte y almacenamiento de sustancias químicas peligrosas.
 - NOM-008-SCFI-2002, Sistema general de unidades de medida. México.
 - NOM-010-STPS-2014, Agentes químicos contaminantes del ambiente laboral- Reconocimiento, evaluación y control.
 - NOM-018-STPS-2015, Sistema para la identificación y comunicación de peligros y riesgos por sustancias químicas peligrosas en los centros de trabajo.

Section 17.- Additional information

This information of Safety Data Sheet is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.



Omega® Tin-Lead-Antimony Solder with Acid Rosin

This material safety data sheet is only for information, consideration and investigation. Omega Aleaciones, S.A. de C.V. not warrant or assume responsibility for the accuracy or correctness of the data content and not responsible for any damage from handling or contact with the above product. Expressly disclaims to the civil liability, loss or damage by the use of this information. Please read the information in this sheet and turn to the person responsible for your company; this as compliance with federal and state laws. This information should be available to any employee who requests it.

